

Model	Zebra 100		Zebra 160		Zebra 320	
Power Source	AC	DC	AC	DC	AC	DC
		110-120v or 220-240v, 50/60Hz	Zebra Zap Pac or Quantum power pack	110-120v, 50/60Hz	Zebra Zap Pac or Quantum power pack	110-120v, 50/60Hz
Flash Output (ws)	100	80**	160	140**	320	260**
Guide No. (ISO 100, m)	30	25**	36	30**	50	42**
Flash Power Control	¼, ½, Full (Switch)		¼, ½, Full (Switch)		¼, ½, Full (Switch)	
Modeling Lamp	60w (E17 Base)	Disabled	60w (E27 Base)	Disabled	100w (E27 Base)	Disabled
Modeling Light Control	On/Off Switch		On/Off Switch		On/Off Switch	
Recycling Time (sec.)	4-6 (Full)	3-5 (Full)	3 (Full)		6-7 (Full)	
	2-3 (½)	1-2 (½)	2 (½)		3-4 (½)	
	1-1.5 (¼)	0.5 (¼)	1 (¼)		1-2 (¼)	
Slave Sensor	Yes		Yes, On/Off Switch		Yes, On/Off Switch	
Safety Protection	Fuse 2A	N/A	Fuse 3A	N/A	Fuse 5A	N/A
Angle Of Illumination	60 degrees		60 degrees		60 degrees	
Accessories Included	AC Power Cord, Sync Cord		AC Power Cord, Sync Cord, Standard Reflector, Protective Cover		AC Power Cord, Sync Cord, Standard Reflector, Protective Cover	
Color Temperature	5600K		5600K		5600K	
Dimensions	4x7.4"		13.4x4.9x9.45" Hexagonal Body		13.4x4.9x9.45" Hexagonal Body	
Weight	17.60 oz		3.5 lbs		3.52 lbs	
Price	\$186.96		\$297.46		\$475.96	

**Based on using the Zebra Zap Pac Battery Pack in DC mode. Depending on the capacity of the type of battery pack used, the Flash Output and Guide No. may have the possibility to reach the same levels as in AC operations.